

Sierra Wireless AirPrime™ Q26 Series Intelligent Embedded Modules

A Single Form Factor for Multiple Technologies

Conceived for rapid mounting on printed circuit boards, the Sierra Wireless AirPrime Q26 Series of intelligent embedded modules allows you to make one single product design which can communicate on any cellular protocol, anywhere around the world. All AirPrime Q26 Series intelligent embedded modules are footprint compatible to smooth product development and simplify upgrading.

Choose an AirPrime Q26 Series intelligent embedded module when you need one or more of the following:

- Programmable capabilities*
- Multi-standard wireless
- Future-proof bearer evolution
- A field replaceable product

SIERRA WIRELESS AIRPRIME Q26 EXTREME INTELLIGENT EMBEDDED MODULE

The dual-mode 2G/3G/3G+ AirPrime Q26 Extreme supports peak data rates up to 7.2 Mbps HSDPA and 2 Mbps HSUPA with automated 2G/3G handover.

SIERRA WIRELESS AIRPRIME Q26 ELITE INTELLIGENT EMBEDDED MODULE

The Q26 Elite features the Qualcomm QSC6055 chipset and integrates Qualcomm gpsOne® technology, making it uniquely suited for fleet management and tracking applications with E911 requirements. It is automotive grade (-40°C to +85°C).

SIERRA WIRELESS AIRPRIME Q2687 INTELLIGENT EMBEDDED MODULE

An automotive-grade (-40°C to +85°C) intelligent embedded module, the Q2687 supports a new parallel data bus for interfacing to displays and external memory, as well as data bearers up to EDGE. Certified for use in the North American market.

SIERRA WIRELESS AIRPRIME Q2686 INTELLIGENT EMBEDDED MODULE

Equipped with on-board audio recording facilities, the Q2686 is well suited for alarm systems and IVR (Interactive Voice Response) product designs. It is automotive grade (-40°C to +85°C).

EMBEDDED SIM

All 3GPP AirPrime Q26 Series products are available with an embedded SIM as an option.

Sierra Wireless's embedded SIM solution removes the plastic from a conventional SIM card and embeds the silicon die inside the intelligent embedded module, with the following benefits:

- Resistance to extreme temperatures, vibration and humidity
- Subscribers can choose their service provider or carrier
- Subscription portability and security
- Reduced size
- Simplified logistics
- Same warranty as the intelligent embedded module itself

* 3GPP versions only



KEY BENEFITS:

- Form-factor compatibility
- High-speed data transmission on any cellular network
- Software designed for M2M
- Remote monitoring and upgrade
- European Union's RoHS compliant
- Manufactured by ISO/TS 16949-certified OEM



AirPrime™

Sierra Wireless Software Suite

Cellular Software for M2M

The Sierra Wireless Software Suite is a comprehensive embedded software platform designed and optimized for M2M (machine-to-machine) communication. The software suite lets you embed your application directly onto your intelligent embedded module.

This embedded software allows Sierra Wireless AirPrime® intelligent embedded modules to function in a number of different ways:

- **Simple modems:** controlled via AT commands by a main processor
- **Intelligent modems:** controlled via AT commands by a main processor, but also providing some additional customized services through a supplementary software application
- **Processors:** the module is the single processor and is hosting your standard ANSI C/C++ application as well as providing the wireless connectivity

The Sierra Wireless Software Suite is owned, developed and maintained by Sierra Wireless, allowing us to respond to your needs faster than companies relying on third-party software. The Sierra Wireless embedded software suite includes:

- A pre-emptive multitasked event-based real-time operating system (Open AT® OS)
- An integrated development environment built on Eclipse™ to develop, compile, download, test and debug your application binary
- An extensive set of additional libraries (Plug-Ins) which offer supplementary services over the core Open AT® OS
- The firmware which manages the wireless communication (GSM/GPRS/EDGE/HSPA) and an AT commands interface in the intelligent embedded module
- A simple and intuitive Windows®-based discovery tool which enables ultra-fast configuration of modules as well as easy access to basic modem features
- PC drivers for Windows® XP/Vista (USB and CMUX Embedded drivers for Windows® Mobile 5.x/6.x and Windows® CE 6.0 (RIL/MUX and USB)

Learning Center

Sierra Wireless provides a professional education program for developers using the Sierra Wireless Software Suite. Enrolling in one of our courses will spark your creativity and help you to speed development time. For companies wishing to enroll a few participants, we provide scheduled training course dates in Europe, North America and Asia on a regular basis. If you have larger needs or just want a dedicated tutoring session, we also offer on-site programs.

Why Sierra Wireless

Sierra Wireless has been in the wireless data and applications business for more than 16 years. We have a proven record of delivering well-designed, highly reliable products, backed by worldwide field and call center support. Our business partners depend on us for a broad portfolio of leading-edge wireless products and solutions that help them extend the reach of their networks. Find out how our products can help you. For more information, visit

www.sierrawireless.com.

Sierra Wireless Services

AirVantage™ Management Services

Once you have deployed your wireless M2M solution in the field, you may need to regularly monitor and upgrade your devices. How do you do that in an easy, safe and cost-effective way?

The answer is AirVantage Management Services, a packaged device management solution which enables remote diagnosis and software upgrades which can save you considerable operating costs.

REMOTE DIAGNOSIS ENABLES YOU TO:

- Run sanity checks and configure your devices
- Monitor the wireless network quality
- Compile traffic reports for analysis

THE SOFTWARE UPGRADE SERVICE INCLUDES:

- Delta generation (download only the code that has changed, for faster downloads and reduced data volume)
- Upgrade for multiple devices
- Real-time campaign monitoring
- Reports

Easy to deploy, secure, scalable and carrier agnostic, AirVantage Management Services are based on industry standards: OMA-DM and full IP architecture.

These secure, easy-to-deploy and scalable device management services are powered by the AirVantage Services Platform, a comprehensive software-as-a-service M2M offering which allows you to quickly expand your M2M services, from device management to asset data management, subscription management and billing services.

AirPrime™ Professional Services

Sierra Wireless proposes an extensive professional services offering:

PRODUCT DESIGN

- Application code review
- Customer design review
- Customer product certification

PRODUCT BUILD

- IMEI implementation
- Tailored delivery
- Tailored product configuration

AFTER SALES

- Intelligent embedded module reconfiguration
- Out of warranty repair
- Extended warranty



KEY BENEFITS:

- Greater solution stability and performance
- Fewer deployment errors, delays and added expenses
- Less time-consuming redesign
- Safer design for the integration of any Sierra Wireless product

Sierra Wireless AirPrime™ Q26 Series Intelligent Embedded Modules

	Q2686	Q2687	Q26 Extreme	Q26 Elite
AIR INTERFACE				
	GSM/GPRS	GSM/GPRS	HSUPA	CDMA 1X RTT
FREQUENCY BANDS				
	GSM/GPRS/EDGE 850/900/1800/1900	GSM/GPRS/EDGE 850/900/1800/1900	GSM 850/900/1800/1900 WCDMA 850/1900/2100	CDMA 1 X RTT/EV-DO REV A 800/1900
APPROVALS				
	R&TTE, CE, GCF, FCC, PTCRB, China	R&TTE, CE, GCF, FCC, PTCRB, China	R&TTE, CE, GCF, FCC, PTCRB, China	FCC, IC, CDG 1&2, various Carrier Approvals
POWER				
Alarm	17uA	17uA	17uA	2mA
Standby and Idle	2,5mA	2,5mA	2,5mA	126mA
GSM/GPRS max	400mA max GPRS class 10	400mA max GPRS class 10	600mA max GPRS class 10	
HSxPA max			820mA max HSDPA full power	
CPU PERFORMANCES				
Processor	ARM946 / DSP	ARM946 / DSP	ARM946 / DSP	ARM9
Core frequency	26-104 MHz	26-104 MHz	26-104 MHz	192 MHz (32 MHz)
User MIPS available	87 MIPS	87 MIPS	87 MIPS	
I/O voltage	1V8-2V8	1V8-2V8	1V8-2V8	1V8-2V8
AUDIO				
Analog audio	2 x speaker out -2 x micro in	2 x speaker out -2 x micro in	2 x speaker out -2 x micro in	2 x speaker out -2 x micro in
Digital audio Codec	HR, FR, EFR, AMR	HR, FR, EFR, AMR	GSM: HR, FR, EFR, AMR W-CMDA: AMR	EVRC/QCELP/4GV (NB) W-CMDA: AMR
Quality	VDA2A	VDA2A	VDA2A	
Echo cancellation & noise reduction	✓	✓	✓	✓
DTMF	✓	✓	✓	✓
INTERFACES				
UART	2	2	X2	2
USB	USB 2.0 Full Speed (12 Mbps)	USB 2.0 Full Speed (12 Mbps)	USB 2.0 Full Speed (12 Mbps)	Device 2.0 (Full Speed)
SPI	2	2	2	
I2C	1	1	1	1
ADC	2	2	2	2
DAC	1	1	1	1
GPIO	Up to 44	Up to 44	Up to 45 GPIO's	Up to 20*
RTC	✓	✓	✓	✓
Timers (HW, SW, Capture)	✓	✓	✓	n/a
Interrupts pins	2	2	3 external interrupt	n/a
Flash LED output	1	1	1	1
PWM (Buzzer)	1	1	1	1
Keyboard interface	5x5	5x5	5x5	5x5
SIM interface	1.8V/3V	1.8V/3V	SIM and U-SIM	RUIM
ANTENNA DIVERSITY				
			✓	
LOCATION SOLUTION				
				gpsOne
EMBEDDED SIM				
	✓	✓		
CONTROL OPTIONS				
	AT commands, C/C++ language; Lua script	AT commands, C/C++ language; Lua script	AT commands, C/C++ language; Lua script	AT commands
OPERATING SYSTEM				
	Open AT®	Open AT®	Open AT®	
MANAGEMENT SERVICES				
	✓	✓	✓	
DRIVERS				
Windows® Mobile	✓	✓	✓	
Windows® CE	✓	✓	✓	
Windows® XP	✓	✓	✓	
Windows® 7	✓	✓	✓	
Windows® Vista	✓	✓	✓	
Mac OS				
Linux	✓	✓	✓	
DEVICE DIMENSIONS				
	32 x 40 x 4 mm	32 x 40 x 4 mm	32 x 40 x 6.55 mm	32 x 40 x 6.63 mm
OPERATIONAL TEMPERATURE				
	-20°C to +55°C	-20°C to +55°C	Class A -20°C to +55°C	-20°C to +55°C
AUTOMOTIVE				
	✓	✓		✓

*1 Multiplexed, *2 with performance deviations